

BRIDGESTONE



RL
(E3, L3)

R-LUG



OFF-THE-ROAD TIRES



The R-LUG bias ply tire offers premium performance on wheel loaders and scrapers.

- ✓ *Non-directional pattern for outstanding rough terrain traction*
- ✓ *Special compounds to resist heat and cutting*
- ✓ *Exceptional cut resistance*

CATEGORY	TIRE SIZE	ARTICLE	PLY RATING	COMPOUND	TRA	AVERAGE WEIGHT	OTD (32ND)	RIM/ FLANGE	OVERALL DIAMETER (IN)	OVERALL WIDTH (IN)	STATIC LOAD RADIUS	STATIC LOADED WIDTH	MIN DUAL SPACING	REVS PER MILE
Small Tube Type	12.00-20	285366	18	CRC	E-3	170	32	8.50V	44.8	12.4	21.1	13.0	15.0	459
	12.00-24	285374	20	D2A	L-3	190	31	8.50V	48.5	12.5	22.0	13.8	15.4	429
	14.00-24	296317	20	E2A	E-3	270	35	11.25/2.0	53.3	15.2	24.7	15.7	20.2	388
	14.00-24	296309	24	E2A	E-3	280	35	10.00W	53.3	14.4	24.7	15.7	17.7	388
	14.00-24	296295	28	E2A	E-3	310	35	10.00W	53.3	14.4	24.7	15.7	17.7	388
Small Tubeless	13.00-24	158795	12	D2A	L-3	190	33	8.00TG	51.5	13.7	23.0	15.4		406
	14.00-24	188426	12	D2A	L-3	220	35	8.00TG	53.3	15.2	24.2	16.1	17.7	390
	17.5-25	425588	12	D2A	L-3	250	37	14.00/1.5	52.9	17.1	23.3	18.4		397
	17.5-25	425605	16	D2A	L-3	270	37	14.00/1.5	52.9	17.1	23.3	18.4		397
	20.5-25	261068	16	D2A	L-3	430	42	17.00/2.0	58.9	20.7	25.7	22.5		358
	23.5-25	261076	16	E1A	E-3	620	55	19.50/2.5	63.9	23.6	29.2	25.5		325
Large Tubeless	23.5-25	261106	20	D2A	L-3	640	55	19.50/2.5	63.9	23.6	29.2	25.5		325
	29.5-25	274291	28	E1A	E-3	1,180	62	25.00/3.5	77.8	30.5	35.0	32.5		268
	29.5-29	421391	28	E2A	E-3	1,290	61	25.00/3.5	77.8	30.5	35.0	32.5		268
	33.25-35	274178	32	E1A	E-3	1,790	62	27.00/3.5	88.3	33.3	38.7	36.7		238
	37.25-35	274267	36	E1A	E-3	2,380	65	31.00/4.0	91.7	37.6	41.7	39.4		227
	37.5-39	274216	44	E1A	E-3	2,670	71	32.00/4.5	100.1	37.8	45.2	41.1		208