BRIDGESTONE

RLS
(E4, L4)

R-LUG S

OFF-THE-ROAD TIRES

BRIDGESTONE

RLS
(E4, L4)
R-LUG S

The R-LUG S bias ply deep tread tire provides premium performance for severe applications requiring additional cut resistance.

- ✔ *Deep non-directional tread pattern*
- ✔ *Special compounds to resist heat and cutting*
- ✔ *Excellent self cleaning tread design*

CATEGORY	TIRE SIZE	ARTICLE	PLY RATING	COMPOUND	TRA	AVERAGE WEIGHT	OTD (32ND)	RIM/ FLANGE	OVERALL DIAMETER (IN)	OVERALL WIDTH (IN)	STATIC LOAD RADIUS	STATIC LOADED WIDTH	MIN DUAL SPACING	REVS PER MILE
Small Tube Type	14.00-24	296457	20	D2A	L-4	340	61	10.00W	55.4	15.2	25.4	17.3		374
Small Tubeless	16.00-25	421499	28	E2A	E-4	560	72	11.25/2.0	60.9	17.7	28.4	18.1	20.2	339
Large Tubeless	26.5-25	275360	20	D2A	L-4	1,070	84	22.00/3.0	70.3	27.6	31.5	29.0		297
	29.5-25	275328	28	D2A	L-4	1,500	94	25.00/3.5	75.3	30.9	32.0	31.7		282
	18.00-33	276049	32	E2A	E-4	950	71	13.00/2.5	73.9	19.8	33.9	20.9	23.1	281
	21.00-35	276081	36	E2A	E-4	1,350	75	15.00/3.0	80.3	23.1	37.4	24.0	27.6	257
	24.00-35	276103	36	E2A	E-4	1,610	83	17.00/3.5	86.6	25.8	39.3	27.4	31.3	240
	24.00-35	276057	42	E2A	E-4	1,670	83	17.00/3.5	86.6	25.8	39.3	27.4	31.3	240
Giant Tubeless	27.00-49	275220	42	E1A	E-4	2,660	88	19.50/4.0	103.9	30.4	48.1	32.4	35.1	199
	27.00-49	276073	42	E2A	E-4	2,660	88	19.50/4.0	103.9	30.4	48.1	32.4	35.1	199
	27.00-49	276146	48	E2A	E-4	2,790	88	19.50/4.0	103.9	30.4	48.1	32.4	35.1	199