

BRIDGESTONE



VELS

(E4)

V-STEEL E-LUG S



OFF-THE-ROAD TIRES



The V-STEEL E-LUG S premium radial tire offers maximum heat dissipation and improved cut resistance for improved productivity and lower operating costs.

- ✓ *Deep non-directional rock tread*
- ✓ *Special compounds provide exceptional wear and cut resistance*
- ✓ *Certain sizes feature low profile, low pressure technologies*

CATEGORY	TIRE SIZE	ARTICLE	PLY RATING	COMPOUND	TRA	AVERAGE WEIGHT	OTD (32ND)	RIM/ FLANGE	OVERALL DIAMETER (IN)	OVERALL WIDTH (IN)	STATIC LOAD RADIUS	STATIC LOADED WIDTH	MIN DUAL SPACING	REVS PER MILE
Small Tubeless	18.00R25	261432	2*	E1A	E-4	830	63	13.00/2.5	64.5	20.3	29.3	22.8	23.1	326
	18.00R25	423637	2*	E2A LS	E-4	840	63	13.00/2.5	64.5	20.3	29.3	22.8	23.1	326
Large Tubeless	18.00R33	275867	2*	E1A	E-4	960	61	13.00/2.5	73.1	20.2	33.7	22.6	23.1	287
	18.00R33	276316	2*	E2A	E-4	960	61	13.00/2.5	73.1	20.2	33.7	22.6	23.1	287
	18.00R33	422177	2*	E2A LS	E-4	960	61	13.00/2.5	73.1	20.2	33.7	22.6	23.1	287
	21/90R33+	424226	2*	E2A LS	E-4	990	61	15.00/3.0	80.5	22.7	36.8	25.6	27.6	261
	21.00R35	275875	2*	E1A	E-4	1,400	74	15.00/3.0	80.5	22.7	36.8	25.6	27.6	261
	21.00R35	276324	2*	E2A	E-4	1,400	74	15.00/3.0	80.5	22.7	36.8	25.6	27.6	261
Giant Tubeless	31/90R49+	424706	2*	E1A	E-4	3,160	84	19.50/4.0	106.1	30.4	48.3	33.9	37.6	198
	31/90R49+	424714	2*	E2A	E-4	3,160	84	19.50/4.0	106.1	30.4	48.3	33.9	37.6	198
	31/90R49+	424722	2*	E2A LS	E-4	3,160	84	19.50/4.0	106.1	30.4	48.3	33.9	37.6	198
	31/90R49+	424730	2*	E3A	E-4	3,160	84	19.50/4.0	106.1	30.4	48.3	33.9	37.6	198
	37.00R57+	424587	2*	E3A LH	E-4	6,050	97	27.00/6.0	133.4	41.1	60.0	46.9	47.9	157
	40.00R57♦	421715	2*	E1A	E-4	7,950	115	29.00/6.0	140.2	44.4	62.3	50.8	51.6	150
	40.00R57+	427339	2*	E1A LH	E-4	7,420	101	29.00/6.0	139.4	43.6	62.0	49.8	53.6	151
	40.00R57♦	418897	2*	E2A	E-4	7,950	115	29.00/6.0	140.2	44.4	62.3	50.8	51.6	150
	40.00R57♦	421723	2*	E2A LS	E-4	7,950	115	29.00/6.0	140.2	44.4	62.3	50.8	51.6	150
	40.00R57♦	419621	2*	E3A	E-4	7,950	115	29.00/6.0	140.2	44.4	62.3	50.8	51.6	150
	40.00R57+	424358	2*	E3A LH	E-4	7,420	101	29.00/6.0	139.4	43.6	62.0	49.8	53.6	151
	46/90R57+	423440	2*	E2A	E-4	8,340	115	29.00/6.0	140.0	45.1	62.1	51.1	52.8	150
	46/90R57+	424390	2*	E2A LS	E-4	8,320	111	29.00/6.0	140.0	45.1	62.1	51.1	55.6	150
	50/90R57	422363	2*	E1A	E-4	10,320	115	34.00/6.5	150.6	50.5	66.7	57.9	61.5	139
	50/90R57	422371	2*	E2A	E-4	10,320	115	34.00/6.5	150.6	50.5	66.7	57.9	61.5	139
	50/90R57	422932	2*	E2A LS	E-4	10,320	115	34.00/6.5	150.6	50.5	66.7	57.9	61.5	139
	50/90R57	422398	2*	E3A	E-4	10,320	115	34.00/6.5	150.6	50.5	66.7	57.9	61.5	139
	59/80R63*	424641	2*	E1A	E-4	11,200	112	44.00/5.0	158.5	57.9	67.3	67.4	70.0	133
	59/80R63*	424668	2*	E2A	E-4	11,200	112	44.00/5.0	158.5	57.9	67.3	67.4	70.0	133

LH Long Haul