

**BRIDGESTONE**



# **VRDP** **(E4)**

V-STEEL ROCK DEEP PREMIUM



OFF-THE-ROAD TIRES



The V-STEEL ROCK DEEP PREMIUM radial tire provides durability and peak performance in hot, rocky conditions utilizing innovative technology for high speed operations.

- ✓ *Rock deep tread provides super cut resistance*
- ✓ *Premium depth for cool running haulage performance*
- ✓ *Innovative narrow grooves that maximize heat dissipation*

CATEGORY	TIRE SIZE	ARTICLE	PLY RATING	COMPOUND	TRA	AVERAGE WEIGHT	OTD (32ND)	RIM/ FLANGE	OVERALL DIAMETER (IN)	OVERALL WIDTH (IN)	STATIC LOAD RADIUS	STATIC LOADED WIDTH	MIN DUAL SPACING	REVS PER MILE
Large Tubeless	27.00R49	427594	2*	E1A	E-4	3,140	96	19.50/4.0	106.7	29.5	48.8	32.9	35.1	197
	27.00R49	427628	2*	E2A	E-4	3,140	96	19.50/4.0	106.7	29.5	48.8	32.9	35.1	197
	27.00R49	427577	2*	E3A	E-4	3,140	96	19.50/4.0	106.7	29.5	48.8	32.9	35.1	197
	27.00R49	427611	2*	LS	E-4	3,140	96	19.50/4.0	106.7	29.5	48.8	32.9	35.1	197
Giant Tubeless	33.00R51	427356	2*	E1A	E-4	4,900	110	24.00/5.0	120.5	36.7	54.2	41.4	42.3	174
	33.00R51	427305	2*	E2A	E-4	4,900	110	24.00/5.0	120.5	36.7	54.2	41.4	42.3	174
	33.00R51	427373	2*	E2A LS	E-4	4,900	110	24.00/5.0	120.5	36.7	54.2	41.4	42.3	174
	33.00R51	427322	2*	E3A	E-4	4,900	110	24.00/5.0	120.5	36.7	54.2	41.4	42.3	174
	40.00R57	424942	2*	E1A	E-4	8,490	122	29.00/6.0	140.7	43.6	62.6	49.8	53.6	149
	40.00R57	424959	2*	E2A	E-4	8,490	122	29.00/6.0	140.7	43.6	62.6	49.8	53.6	149
	40.00R57	424925	2*	E2A LS	E-4	8,490	122	29.00/6.0	140.7	43.6	62.6	49.8	53.6	149
	40.00R57	424908	2*	E3A	E-4	8,490	122	29.00/6.0	140.7	43.6	62.6	49.8	53.6	149
	42/90R57	425299	2*	E2A	E-4	7,180	122	27.00/6.0	136.1	41.7	60.6	47.7	50.1	154
	42/90R57	425316	2*	E2A LS	E-4	7,180	122	27.00/6.0	136.1	41.7	60.6	47.7	50.1	154
	42/90R57	425333	2*	E3A	E-4	7,180	122	27.00/6.0	136.1	41.7	60.6	47.7	50.1	154
	46/90R57	424625	2*	E1A	E-4	8,800	122	29.00/6.0	140.7	45.1	62.4	51.1	55.6	149
	46/90R57	424560	2*	E2A	E-4	8,800	122	29.00/6.0	140.7	45.1	62.4	51.1	55.6	149
	46/90R57	424633	2*	E3A	E-4	8,800	122	29.00/6.0	140.7	45.1	62.4	51.1	55.6	149
	53/80R63	427186	2*	E1A	E-4	10,050	139	36.00/5.0	150.9	51.2	65.2	59.5	64.0	139
	53/80R63	427220	2*	E2A	E-4	10,050	139	36.00/5.0	150.9	51.2	65.2	59.5	64.0	139
	53/80R63	427237	2*	E2A LS	E-4	10,050	139	36.00/5.0	150.9	51.2	65.2	59.5	64.0	139
	53/80R63	427203	2*	E3A	E-4	10,050	139	36.00/5.0	150.9	51.2	65.2	59.5	64.0	139
	55/80R63	427747	2*	E1A	E-4	11,200	139	41.00/5.0	154.0	55.1	65.8	65.0	68.5	136
	55/80R63	427781	2*	E2A	E-4	11,200	139	41.00/5.0	154.0	55.1	65.8	65.0	68.5	136
55/80R63	427798	2*	E2A LS	E-4	11,200	139	41.00/5.0	154.0	55.1	65.8	65.0	68.5	136	
55/80R63	427764	2*	E3A	E-4	11,200	139	41.00/5.0	154.0	55.1	65.8	65.0	68.5	136	