

Firestone



SDT LD **(L5)**

SUPER DEEP TREAD
LOADER DOZER



OFF-THE-ROAD TIRES



The SUPER DEEP TREAD LOADER DOZER bias tire offers 250% deeper tread than L3 patterns providing greater casing protection and longer service life. Certain sizes available with “steel shield” construction for added cut and impact protection.

- ✓ *Super heavy duty non-directional rock service tread design*
- ✓ *Some sizes available in “steel shield” construction for additional cut and impact protection*
- ✓ *Extra tread depth is 250% deeper than our SRG LD (L3)*

CATEGORY	TIRE SIZE	ARTICLE	PLY RATING	COMPOUND	TRA	AVERAGE WEIGHT	OTD (32ND)	RIM/ FLANGE	OVERALL DIAMETER (IN)	OVERALL WIDTH (IN)	STATIC LOAD RADIUS	STATIC LOADED WIDTH	MIN DUAL SPACING	REVS PER MILE
Small Tubeless	17.5-25	426115	16		L-5	540	80	14.00/1.5	55.1	17.5	24.5	19.4		380
	17.5-25	426132	20		L-5	490	80	14.00/1.5	55.1	17.5	24.5	19.4		380
	20.5-25	403903	16		L-5	610	88	17.00/2.0	60.9	20.7	27.8	23.4		341
	20.5-25	417610	20		L-5	670	88	17.00/2.0	60.9	20.7	27.8	23.4		341
	23.5-25	403911	16		L-5	800	98	19.50/2.5	65.9	24.4	30.3	27.6		314
	23.5-25	403970	20		L-5	850	98	19.50/2.5	65.9	24.4	30.3	27.6		314
Large Tubeless	26.5-25	403989	20		L-5	1,130	108	22.00/3.5	71.1	27.0	32.3	30.5		293
	26.5-25	416428	26		L-5	1,200	108	22.00/3.5	71.1	27.0	32.3	30.5		293
	29.5-25	413984	22		L-5	1,480	127	25.00/3.5	74.9	29.9	33.4	33.8		279
	29.5-25	416436	28		L-5	1,580	127	25.00/3.5	74.9	29.9	33.4	33.8		279
	29.5-29	403962	28		L-5	1,720	127	25.00/3.5	80.1	30.5	36.3	34.5		260
	65/35-33	416649	30		L-5	2,330	120	28.00/3.5	82.8	33.8	38.3	37.5		250
	65/35-33	427832	42	NS	L-5	2,740	120	28.00/3.5	82.8	33.8	38.3	37.5		250
	41.25/70-39	417033	42		L-5	4,110	146	32.00/4.5	98.7	40.9	45.1	43.8		210
	41.25/70-39	416789	42	NS	L-5	4,500	146	32.00/4.5	98.7	40.9	45.1	43.8		210
	65/40-39	280159	36		L-5	3,350	134	32.00/4.0	94.9	38.6	43.3	42.8		219
Giant Tubeless	65/45-45	427713	58		L-5	5,000	150	36.00/4.5	108.1	43.1	49.4	47.8		192
	65/45-45	427730	58		L-5	5,660	150	36.00/4.5	108.1	43.1	49.4	47.8		192
	49.5/85-57*	420476	76		L-5	11,820	153	36.00/6.0	155.6	49.8	69.0	-		135
	53.5/85-57*	420468	76		L-5	12,420	153	44.00/6.0	152.2	53.8	68.3	57.8		135
	53.5/85-57*	480150	76	NS	L-5	12,810	153	44.00/6.0	152.2	53.8	68.3	57.8		135

NS = Nylon Steel