

# Firestone



## **SGG/SGG LD** **(E2, L2 & E2/L2)**

SUPER GROUND GRIP



OFF-THE-ROAD TIRES

## SGG/SGG LD (E2, L2 & E2/L2) SUPER GROUND GRIP



The SUPER GROUND GRIP bias ply tire features a self-cleaning directional tread design for earthmover, loader/dozer and grader applications offers exceptional flotation and traction in soft soil or mud environments.

- ✓ *Self-cleaning tread design*
- ✓ *Directional tread pattern with armored sidewalls*
- ✓ *Exceptional flotation and traction in soft soil or mud*

CATEGORY	TIRE SIZE	ARTICLE	PLY RATING	COMPOUND	TRA	AVERAGE WEIGHT	OTD (32ND)	RIM/ FLANGE	OVERALL DIAMETER (IN)	OVERALL WIDTH (IN)	STATIC LOAD RADIUS	STATIC LOADED WIDTH	MIN DUAL SPACING	REVS PER MILE
Small Tubeless	15.5-25	425248	12	LD	L-2	180	29	12.00/1.5	50.0	15.8	22.3	17.9		418
	15.5-25	425265	12	LD CRC	L-2	180	29	12.00/1.5	50.0	15.8	22.3	17.9		418
	17.5-25	425129	12	LD	L-2	220	31	14.00/1.5	53.6	18.0	23.7	20.3		391
	17.5-25	425180	16	LD	L-2	240	31	14.00/1.5	53.6	18.0	23.7	20.3		391
	20.5-25	405175	12	LD	L-2	330	35	17.00/2.0	58.5	21.0	25.8	23.7		359
	20.5-25	408492	16	LD	L-2	350	35	17.00/2.0	58.5	21.0	25.8	23.7		359
	20.5-25	410713	20	LD	L-2	370	35	17.00/2.0	58.5	21.0	25.8	23.7		359
	23.5-25	405183	12	LD	L-2	450	39	19.50/2.5	63.4	24.1	28.9	26.6		328
	23.5-25	405221	16	LD	L-2	470	39	19.50/2.5	63.4	24.1	28.9	26.6		328
23.5-25	404969	20	LD	E2/L2	490	39	19.50/2.5	63.5	23.7	27.9	26.8		331	
Large Tubeless	26.5-25	405272	20	LD	L-2	720	43	22.00/3.0	69.4	26.7	30.8	30.2		302
	29.5-25	404810	22	LD	E2/L2	880	47	25.00/3.5	74.3	30.3	33.2	33.7		281

LD=Loader/Dozer