

Firestone



SRG DT **(E4)**

SUPER ROCK GRIP DEEP TREAD



OFF-THE-ROAD TIRES



The SUPER ROCK GRIP DEEP TREAD bias tire is designed for a variety of haulage trucks, with certain sizes designed to withstand heavy loads and scorching temperatures of slab and slag carriers.

- ✓ *Extra-heavy duty non-directional rock service design*
- ✓ *Exceptional off-road traction*
- ✓ *Extra deep tread design provides excellent resistance to impacts and cuts*

CATEGORY	TIRE SIZE	ARTICLE	PLY RATING	COMPOUND	TRA	AVERAGE WEIGHT	OTD (32ND)	RIM/ FLANGE	OVERALL DIAMETER (IN)	OVERALL WIDTH (IN)	STATIC LOAD RADIUS	STATIC LOADED WIDTH	MIN DUAL SPACING	REVS PER MILE
Small Tubeless	16.00-25	403245	24		E-4	530	62	11.25/2.0	60.2	17.2	28.2	18.9	20.2	342
	16.00-25	423149	28		E-4	560	62	11.25/2.0	60.2	17.2	28.2	18.9	20.2	342
	18.00-25	403172	32		E-4	730	69	13.00/2.5	64.5	20.0	30.1	22.5	23.1	320
Large Tubeless	18.00-33	414972	32	CRC	E-4	930	69	13.00/2.5	72.9	20.3	34.1	22.6	23.1	283
	21.00-35	414131	36	CRC	E-4	1,270	67	15.00/3.0	80.1	22.9	37.1	26.3	27.6	258
	24.00-35	414905	42	CRC	E-4	1,700	71	17.00/3.5	85.6	25.9	39.5	29.6	31.3	242
	33.25-35	413380	38		E-4	2,140	86	27.00/3.5	89.2	34.0	40.1	38.2		234
	37.25-35	413623	36		E-4	2,560	91	31.00/4.0	95.3	37.2	42.2	42.0		220
	37.5-39	172278	44		E-4	3,050	91	32.00/4.5	100.3	38.0	45.1	43.0		208
Giant Tubeless	24.00-49	403504	42		E-4	2,000	71	17.00/3.5	99.6	25.9	46.5	29.6	31.3	207
	27.00-49	416479	42		E-4	2,540	79	19.50/4.0	106.0	30.4	49.3	34.2	35.1	195
	33.00-51	415677	58		E-4	4,560	93	24.00/5.0	120.5	36.0	55.8	40.8	42.3	172
	36.00-51	414832	58		E-4	5,370	104	26.00/5.0	127.3	39.6	58.5	44.7	46.6	163
	40.00-57*	424773	76		E-4	7,720	104	29.00/6.0	141.5	43.8	65.1	48.8	51.6	153